



ADVANCED SUBSIDIARY (AS)
General Certificate of Education
2018

Physics
Assessment Unit AS 1
assessing
Forces, Energy and Electricity
[SPH11]

TUESDAY 15 MAY, MORNING

**MARK
SCHEME**

			AVAILABLE MARKS
1	(a) $P = VI$ 18 = 9.6I $I = 1.9 \text{ (1.875) (A)}$	[1] [1] [1]	[3]
	(b) $E = VIt$ or Pt Conversion of t to seconds (660) $E = 12000 \text{ (J)}$ ecf for I (SE t in minutes 198 J scores [2])	[1] [1] [1]	[3]
	(c) $I = nq/t$ or $Q = It$ or $Q = \frac{W}{V}$ $n = \frac{W}{eV}$ (ecf E) $1.9 = n(1.6 \times 10^{-19})/(660)$ or $Q = 1241 \text{ (C)}$ $n = 7.7 \times 10^{21}$ or 7.8×10^{21} ecf for I, t	[1] [1] [1]	[3] 9
2	(a) I proportional to V Provided temperature constant	[1] [1]	[2]
	(b) (i) Lamp in series with cell Variable resistor (or power pack) Ammeter in series, Voltmeter across lamp	[1] [1] [1] [1]	[4]
	(ii) Record current and voltage Adjust (using variable resistor) ≥ 5 sets of results	[1] [1] [1]	[3]
	(iii) Curve, starting at (0,0) Correct sense	[1] [1]	[2]
	(c) Larger current (or V) temperature increases Resistance of metal filament increases with temperature $R = \frac{V}{I}$ so graph gets less steep	[1] [1] [1]	[3] 14
3	(a) Calculates 13 cm } can be on diagram 25(9.81) $F(22) = 25(9.81)(13)$ $F = 145 \text{ N}$	[1] [1] [1] [1]	[4]
	(b) F is always to the right of (front) wheels/inside base/between wheels No anticlockwise moment	[1] [1]	[2] 6
4	(a) $9.4 \times 10^{27} \text{ Tm}^3 = 9.4 \times 10^{63} \text{ m}^3$ $1.8 \times 10^{13} \text{ Gg} = 1.8 \times 10^{19} \text{ kg}$ Density = $1.9 \times 10^{-45} \text{ kg m}^{-3}$ (ecf their m and V) To 2 s.f.	[1] [1] [1] [1]	[4]
	(b) Base unit of F = kg m s^{-2} Base unit of v = m s^{-1} Base unit of B = s kg^{-1}	[1] [1] [1]	[3] 7

			AVAILABLE MARKS
5	(a) (i) $24.9 \cos 38$ 19.6 (kN) 2000 kg	[1] [1] [1] [3]	
	(ii) $24.9 \sin 38$ 15.3 kN S.E. sin, cos reversed max $\frac{3}{5}$	[1] [1] [2]	
	(b) Momentum vector, Ke scalar Vectors have an associated direction	[1] [1] [1] [3]	8
6	(a) $s = ut + \frac{1}{2}at^2$ eqn Either: $22.5 = 2.5(7) + \frac{1}{2}(a)(7)^2$ subs $a = 0.204 \text{ km h}^{-2}$ $a = \frac{0.204 \times 1000}{(3600)^2}$ or $22500 = 2500(t) + \frac{1}{2}(a)(t)^2$ conv km – m and any correct subs of s, u and t $22500 = 2500(7) + \frac{1}{2}(a)(7 \times 3600)^2$ time subs $a = 1.57 \times 10^{-5} \text{ ms}^{-2}$ ans	[1] [1] [1] [1] [1] [1] [1] [4]	
	(b) (i) $v^2 = u^2 + 2as$ $0 = u^2 + 2(-1.2 \times 10^{-3})(950)$ } eqn or subs $u = 1.51 \text{ m s}^{-1}$ $1.51^2 + 0.49^2 = v^2$ (ecf u) $v = 1.59$ angle = 72° (ecf v)	[1] [1] [1] [1] [1] [5]	
	(ii) $v = u + at$ eqn $t_v = 1.26 \times 10^3 \text{ s}$ ans Total time = $2 t_v (2.52 \times 10^3)$ $s = vt$ $s = 1233 \text{ m}$	[1] [1] [1] [1] [5]	14
7	(a) $KE = 0.5mv^2$ $v^2 = 25^2 (\text{m s}^{-1})$ and $m = 1940 \text{ (kg)}$ subs $KE = 6.06 \times 10^5 \text{ (J)}$	[1] [1] [1] [3]	
	(b) (i) $t = 180 \times 10^3 / 8.3 = 2.17 \times 10^4 \text{ s}$ $P = 0.12(96) = 11.52 \text{ (kW)}$ $E = Pt = (11.52 \times 10^3)(2.17 \times 10^4)$ $E = 2.5 \times 10^8 \text{ (J)}$	[1] [1] [1] [1] [4]	
	(ii) $E \text{ input} = 3.3 \times 10^8$ (ecf b(i)) or $0.75 (3.6 \times 10^6)$ Units used = $(3.33 \times 10^8) / (3.6 \times 10^6) = 92.6$ Cost = £14.81	[1] [1] [1] [3]	
	(c) To reduce CO_2 emissions (international commitment)/harmful gas emissions/atmospheric pollution To conserve supplies of fossil fuels/reduction in use	[1] [1] [2]	12

			AVAILABLE MARKS
8	(a) Statement of first law Reference to 'resultant' Comparison: resultant force is zero on both objects Contrast: rock has no force acting on it car driving force = air resistance or resistive forces	[1] [1] [1] [1] [1]	[5]
	(b) Statement of Newton's 3rd law e.g. $ F_{\text{earth}} = F_{\text{beam}} $ or $f = ma$ 1619 (N) from $f = ma$ $2.71 \times 10^{-22} \text{ (m s}^{-2}\text{)}$ Direction: upwards/towards the beam	[1] [1] [1] [1]	[4] 9
9	(a) $p = mv$ $p = (57 \times 10^{-3})(-18)$ $p = (-)1.03 \text{ (kg m s}^{-1}\text{)}$	[1] [1] [1]	[3]
	(b) Impulse = area under graph $\text{Impulse} = \frac{1}{2}(0.6)(8.2)$ $\text{Impulse} = 2.46 \text{ (N s)}$	[1] [1] [1]	[3]
	(c) $Ft = mv - mu$ $2.46 = 0.057[(v) - (-18)]$ $v = 25 \text{ (m s}^{-1}\text{)}$ (using 2.5 N s gives 26 m s^{-1})	[1] [1] [1]	[3] 9
10	(a) (i) Opposition to current flow within the cell	[1]	
	(ii) $1.38 = 1.52 - (0.636)r$ correct subs $r = 0.220 \text{ (\Omega)} = 220 \text{ m}\Omega$	[1] [1]	[2]
	(b) (i) $\frac{1}{R_{\text{effective}}} = \frac{1}{6} + \frac{1}{4}$ $R_{\text{effective}} = 2.4 \text{ \Omega}$ $R_{\text{lower}} = 2.4 + 4.6 = 7 \text{ \Omega}$ (ecf 2.4) $R_{\text{upper}} = 4.5 + 2.5 = 7 \text{ \Omega}$ $R_{\text{total}} = 3.5 \text{ \Omega}$ (ecf R_{lower})	[1] [1] [1] [1] [1]	[5]
	(ii) $R_{\text{total}} + R_{\text{internal}} = 3.8 \text{ \Omega}$ (ecf R_{total}) $I_{\text{total}} = \frac{V}{R} = \frac{1.52}{3.8(\text{ecf})} = 0.4A$	[1]	[2]
	(iii) $I_{\text{lower}} = 0.2A$ (ecf 0.5 I_{total}) $I_{6 \Omega} = 0.08$ (ecf $0.4 \times I_{\text{lower}}$)	[1] [1] [1]	[2] 12
		Total	100