CAMBRIDGE INTERNATIONAL EXAMINATIONS

Cambridge International Advanced Subsidiary and Advanced Level

MARK SCHEME for the May/June 2015 series

9702 PHYSICS

9702/41 Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2015 series for most Cambridge IGCSE®, Cambridge International A and AS Level components and some Cambridge O Level components.

CAMBRIDGE
International Examinations

Section A

1	**(a)**	(gravitational) force proportional to product of masses and inversely proportional to square of separation	M1	
		reference to *either* point masses *or* particles *or* 'size' much less than separation	A1	[2]
	(b)	gravitational force provides/is the centripetal force	B1	
		$GM_Nm / r^2 = mr\omega^2$ (or mv^2 / r)	M1	
		$2\pi / T$ (*or* $v = 2\pi r / T$) leading to $GM_N = 4\pi^2r^3 / T^2$	A1	[3]
	(c)	$M_N / M_U = (3.55 / 5.83)^3 \times (13.5 / 5.9)^2$		
		x^3 factor correct	C1	
		T^2 factor correct	C1	
		ratio = 1.18 (*allow 1.2*)	A1	
		alternative method: mass of Neptune = 1.019×10^{26} kg	(C1)	
		mass of Uranus = 8.621×10^{25} kg	(C1)	
		ratio = 1.18	(A1)	[3]
2	**(a)**	(sum of) potential energy and kinetic energy of molecules/atoms/particles	M1	
		mention of random motion/distribution	A1	[2]
	(b) (i)	$pV = nRT$		
		either at A, $1.2 \times 10^5 \times 4.0 \times 10^{-3} = n \times 8.31 \times 290$		
		or at B, $3.6 \times 10^5 \times 4.0 \times 10^{-3} = n \times 8.31 \times 870$	C1	
		n = 0.20 mol	A1	[2]
	(ii)	$1.2 \times 10^5 \times 7.75 \times 10^{-3} = 0.20 \times 8.31 \times T$ *or* $T = (7.75 / 4.0) \times 290$	C1	
		T = 560 K	A1	[2]
		(*Allow tolerance from graph*: 7.7–7.8 $\times 10^{-3}$ m^3)		
	(c)	temperature changes/decreases so internal energy changes/decreases	B1	
		volume changes (at constant pressure) so work is done	B1	[2]
3	**(a)**	(numerically equal to) quantity of (thermal) energy/heat to change state/phase of unit mass	M1	
		at constant temperature	A1	[2]
		(*allow 1/2 for definition restricted to fusion or vaporisation*)		
	(b) (i)	at 70 W, mass s^{-1} = 0.26 g s^{-1}	A1	
		at 110 W, mass s^{-1} = 0.38 g s^{-1}	A1	[2]

		(ii)	**1.** $P + h = mL$ or substitution of one set of values	C1	
			$(110 - 70) = (0.38 - 0.26)L$	C1	
			$L = 330\,\text{J g}^{-1}$	A1	[3]
			2. *either* $70 + h = 0.26 \times 330$		
			or $110 + h = 0.38 \times 330$	C1	
			h = 17 / 16 / 15 W	A1	[2]
4	**(a)**	**(i)**	frequency at which object is made to vibrate/oscillate	B1	[1]
		(ii)	frequency at which object vibrates when free to do so	B1	[1]
		(iii)	maximum amplitude of vibration of oscillating body	B1	
			when forced frequency equals natural frequency (of vibration)	B1	[2]
	(b)	e.g.	vibration of quartz/piezoelectric crystal (*what is vibrating*)	M1	
			either for accurate timing		
			or maximise amplitude of ultrasound waves (*why it is useful*)	A1	[2]
	(c)	e.g.	vibrating metal panels (*what is vibrating*)	M1	
			either place strengthening struts across the panel		
			or change shape/area of panel (*how it is reduced*)	A1	[2]
5	**(a)**		(magnitude of electric field strength is the potential gradient	B1	
			use of gradient at $x = 4.0\,\text{cm}$	M1	
			gradient = $4.5 \times 10^4\,\text{N C}^{-1}$ (*allow* $\pm 0.3 \times 10^4$)	A1	
			or		
			$V = \dfrac{Q}{4\pi\varepsilon_0 x}$ and $E = \dfrac{Q}{4\pi\varepsilon_0 x^2}$ leading to $E = \dfrac{V}{x}$	(B1)	
			$E = 1.8 \times 10^3 / 0.04$	(M1)	
			$= 4.5 \times 10^4\,\text{N C}^{-1}$	(A1)	[3]
	(b)	**(i)**	$3.6 \times 10^3\,\text{V}$	A1	[1]
		(ii)	capacitance $= Q / V$	C1	
			$= (8.0 \times 10^{-9})/(3.6 \times 10^3)$		
			$= 2.2 \times 10^{-12}\,\text{F}$	A1	[2]
6	**(a)**	**(i)**	gravitational	B1	[1]
		(ii)	gravitational and electric	B1	[1]
		(iii)	magnetic and one other field given	B1	
			magnetic, graviational and electric	B1	[2]

(b)	**(i)**	out of (plane of) paper/page (*not "upwards"*)	B1	[1]
	(ii)	$B = mv / qr$	C1	
		$= (3.32 \times 10^{-26} \times 7.6 \times 10^{4}) / (1.6 \times 10^{-19} \times 6.1 \times 10^{-2})$	C1	
		$= 0.26\,\text{T}$	A1	[3]
(c)		sketch: semicircle with diameter < 12.2 cm	B1	[1]

7	**(a)**	can change (output) voltage efficiently *or* to suit different consumers/appliances	B1	
		by using transformers	B1	[2]
	(b)	for same power, current is smaller	B1	
		less heating in cables/wires *or* thinner cables possible *or* less voltage loss in cables	B1	[2]

8	**(a)**	**(i)**	$p = h / \lambda$		
			$= (6.63 \times 10^{-34}) / (6.50 \times 10^{-12})$	C1	
			$= 1.02 \times 10^{-22}\,\text{N s}$	A1	[2]
		(ii)	$E = hc / \lambda$ *or* $E = pc$		
			$= (6.63 \times 10^{-34} \times 3.00 \times 10^{8}) / (6.50 \times 10^{-12})$	C1	
			$= 3.06 \times 10^{-14}\,\text{J}$	A1	[2]
	(b)	**(i)**	$0.34 \times 10^{-12} = (6.63 \times 10^{-34}) / (9.11 \times 10^{-31} \times 3.0 \times 10^{8}) \times (1 - \cos\theta)$	C1	
			$\theta = 30.7°$	A1	[2]
		(ii)	deflected electron has energy	M1	
			this energy is derived from the incident photon	A1	
			deflected photon has less energy, longer wavelength (so $\Delta\lambda$ always positive)	B1	[3]

9	**(a)**		nucleus/nuclei emits	M1	
			spontaneously/randomly	A1	
			α-particles, β-particles, γ-ray photons	A1	[3]
	(b)	**(i)**	$N - \Delta N$	A1	[1]
		(ii)	$\Delta N / \Delta t$	A1	[1]
		(iii)	$\Delta N / N$	A1	[1]
		(iv)	$\Delta N / N\Delta t$	A1	[1]
	(c)		graph: smooth curve in correct direction starting at (0,0)	M1	
			n at $2t_{½}$ is 1.5 times that at $t_{½}$ (± 2 mm)	A1	[2]

Section B

10	**(a)**	**(i)**	(potential =) 1.2 / (1.2 + 4.2) × 4.5 = +1.0 V	A1	[1]
		(ii)	(for V_{IN} > 1.0 V) $V^+ > V^-$	B1	
			output (of op-amp) is +5 V or positive	M1	
			diode conducts giving +5 V across R or V_{out} is +5 V	A1	
			(for V_{IN} < 1.0 V) output of op-amp –5 V / negative so diode does not conduct, giving V_{out} = 0 or 0 V across R	A1	[4]
	(b)	**(i)**	square wave with maximum value +5 V and minimum value 0	M1	
			vertical sides in correct positions and correct phase	A1	[2]
		(ii)	re-shaping (digital) signals/regenerator (amplifier)	B1	[1]
11	**(a)**		change/increase/decrease anode/tube voltage	B1	
			electrons striking <u>anode</u> have changed (kinetic) energy/speed	B1	
			X-ray/photons/beam have different wavelength/frequency	B1	[3]
	(b)	**(i)**	$I = I_0 e^{-\mu x}$	B1	[1]
		(ii)	contrast is difference in degree of blackening (of regions of the image)	B1	
			μ (very) similar so similar absorption of radiation (for same thickness) so little contrast	A1	[2]
12	**(a)**	**(i)**	loudspeaker/doorbell/telephone etc.	B1	[1]
		(ii)	television set/audio amplifier etc.	B1	[1]
		(iii)	satellite/satellite dish/mobile phone etc.	B1	[1]
	(b)		e.g. lower attenuation/fewer repeaters more secure less prone to noise/interference physically smaller/less weight lower cost greater bandwidth (*any two sensible suggestions, 1 each*)	B2	[2]
	(c)	**(i)**	ratio = 25 + (62 × 0.21)	C1	
			= 38 dB	A1	[2]
		(ii)	ratio / dB = 10 lg (P_2 / P_1)	C1	
			38 = 10 lg (P / {9.2 × 10^{-6}})		
			P = 58 mW or 5.8 × 10^{-2} W	A1	[2]
			(*allow 1/2 for missing 10 in equation*)		

13	**(a)**	**(i)**	to align nuclei/protons	B1	
			to cause Larmor/precessional frequency to be in r.f. region	B1	[2]
		(ii)	Larmor/precessional frequency depends on (applied magnetic) field strength	B1	
			knowing field strength enables (region of precessing) nuclei to be located	M1	
			by knowing the frequency	A1	[3]
	(b)		$E = 2.82 \times 10^{-26} \times B$		
			$6.63 \times 10^{-34} \times 42 \times 10^{6} = 2.82 \times 10^{-26} \times B$	C1	
			$B = 0.99\,\text{T}$	A1	[2]